

JOYALL[®] TYRES

Ride With The Best



A8
STEER
★★★★★

★Premium steer tyre
& Extra tread width

★Perfect balancing
for steer

★Exceptional
mileage



★Comfortable
ride & low noise

★Resistance to
irregular wear

★Proven in
Australian
conditions

TECHNICAL SPECIFICATIONS

TYRE SIZE	PLY RATING	PATTERN DESCRIPTION	TREAD DEPTH		RIM	TUBE TYPE	LI/S.S.	OVERALL DIAMETE R (mm)	TREAD WIDTH (mm)	INFLATION PRESSURE (kPa)		LOAD CAPACITY (kg)	
			MM	1/32 Inch						SINGLE	DUAL	SINGLE	DUAL
11R22.5	16PR	FREEWAY STEER	16.50	20.8	8.25	TL	146/143L	1050	220	830	830	3000	2725
12R22.5	18PR	FREEWAY STEER	16.50	20.8	9.00	TL	152/149L	1081	236	930	930	3550	3250
295/80R22.5	16PR	FREEWAY STEER	16.50	20.8	9.00	TL	150/147M	1042	236	830	830	3350	3075
295/80R22.5	18PR	FREEWAY STEER	16.50	20.8	9.00	TL	152/149M	1042	236	900	900	3550	3250
315/80R22.5	18PR	FREEWAY STEER	15.00	18.9	9.00	TL	151/148L	1014	253	830	830	3450	3150
315/80R22.5	20PR	FREEWAY STEER	16.50	20.8	9.00	TL	154/151M	1070	253	830	830	3750	3450

★★★